



RECOMMENDED RIB DIMENSIONS
(FOR REFERENCE ONLY)

Notes:

1. Part to fit in a $4.75 \pm 0.25 \times 16.0$ slot in a 1.5-5.5 thick plastic panel ;
2. Performance when tested in a 4.75mm slot x 3.0 thick plastic panel :
Insertion: 50N Max.
Extraction: 60N Min.
3. General tolerances: ± 0.5 ;
4. RoHS compliant .

Part No.	Article No.	Material	Color
10079	GW716169	POM UL94HB	Orange
10098	GW716169N		Natural

Gecko International Co.						DATE	2023-5-22	DIMENSION	L ≤ 4	TOLERANCE	±0.10
TITLE	TRIM PANEL CLIP					SCALE	FIT	L ≤ 4	±0.10		
ARTICLE NO.	GW716169	MOLD NO.	S1102	DRAW	PLK	UNIT	MM	4 < L ≤ 15	±0.20		
PART NO.	SEE TABLE	MATERIAL	SEE TABLE	DESIGN	PLK	VERSION	A0	15 < L ≤ 50	±0.30		
DWG NO.	E1085	COLOR	SEE TABLE	APPROVAL	FDL	VIEW		50 < L ≤ 100	±0.40		